


MODEL	TIERS	WIDTH(A)	HEIGHT (B)		PITCH (C)	1. FLOOR HEIGHT FROM THE GROUND (X)
EU20	4 TIERS	1550	3180		650	300
EU20	5 TIERS	1550	3830		650	300
EU20	6 TIERS	1550	4480		650	300
EU20	7 TIERS	1550	5130		650	300
EU20	8 TIERS	1550	5780		650	300
EU20	8 TIERS WITH CATWALK	1550	6410	B1 3000	650	300
				B2 3210		
EU20	12 TIERS WITH CATWALK	1550	9640	B3 3000	650	300
				B4 3030		
				B5 3210		



MODEL	DIMENSIONS OF SECTION (mm)	SURFACE AREA IN SECTION (cm ²)	NUMBER OF LAYER IN EACH SECTION	AREA PER LAYER (cm ²)	FEEDING AREA PER LAYER (cm)
EU-20	2400 X 625	15.000	20	750	12

GÜRES TECHNOLOGY

EU-20 ENRICHED LAYER CAGE



We know-how!



Telephone: +90 236 357 22 12 **Fax:** +90 236 357 22 92
E-Mail: teknoloji@gures.com.tr **Web:** www.guresteknoloji.com.tr
Address: İstasyon Mah. İzmir - İstanbul yolu üzeri 3.km No:29 Saruhanlı / MANİSA / TURKEY

f /guresteknoloji

▶ guresteknoloji

in /company/guresteknoloji

EU-20 ENRICHED LAYER CAGE

High quality and maximum performance



We know-how!

Güres Technology, as a part of Güres Group, which has the largest full integrated egg production facility of Turkey, established in 2002 with half-century experience. With 20.000 m2 production area and of 8.700 m2 R & D operating area Güres Technology became one of the most reliable companies over 25 countries as one of the leading cage manufacturers of Turkey. We, Güres Technology trust our technological infrastructure, wide product range, experienced R&D team and energetic staff, and we ready to share our technical wealth and experience with our customers.



Appropriate to European Union Animal Welfare Standard

- In dimension 2400 x 625 mm section of cage
- For each bird there is 15 cm PVC perching area and 12 cm feeding space appropriate for poultry nature. There is also a curtained nest box, scratching carpet and nail shortener located in each section.

** Enriched Cage System which produced by Güres Technology, complies with animal welfare and EU directive 1999/74 dated 19 July 1999.*

Cage With Reinforced Construction

- 2 mm thick cage leg on each 60 cm.
- Secured with steel dowels on each 6 meter.
- Ø 60 mm metal shoes are used at the places where the cage legs are pressed on the ground.



Smooth And Fast Installation

- Fully automated cage system can be installed up to 8 tiers without catwalk and up to 12 tiers with catwalk.
- Cage batteries scaled with calibrated digital measuring devices
- On-site inspection, on-time installation with experienced discovery and assembly team

Minimum Crack Maximum Hygiene!

- Fully automated lift or elevator egg collection alternatives.
- Antistatic, non-elongated, special PP egg belts
- Maximum cleaning with special belt brush system
- Cleaner eggs with manure-free bottom wire design
- 90 degree pivotable, direct conveyor system
- With Chain egg conveyor system, not with pipe!

Low Feed Loss With Perfect Feeding Systems

- Trolley or chain feeding system alternatives
- 4 stage feed distribution devices
- Homogenous feed distribution
- Strong feed trough with special double curved design



- All cages have automatic drinking and manure removal systems.
- There are 8 red imported nipples and V type drop holders in each two sections.
- There is a PP manure band extending along the cage, under each cage row and tier.
- Each tier has rollers and scrapers.

